

# AU-200 USB LCD Phone



## HARDWARE

- MCU: 4MHz
- Standard USB1.1 connector
- Built-in 16 bit sound card
- Dual channel sound effect controller, available to connect external stereo earphone + MIC.
- Built-in 20KHz bandwidth loudspeaker
- LCD backlight four row display

## KEY FEATURES

- Available to be used as "USB sound card + speaker cabinet" under hands free mode.
- Mute, Hands free function
- User define ring tone.
- Multiple languages display
- Friend list display, on-line friends display
- Inquiry of missed call/received calls/dialled calls and the conversation time
- Statistic of Missed calls
- Call ID display
- Directly dial Skype, Skypeout number
- Redial/dial back function
- Replacing mouse to operate SKYPE software in computer
- Skypeout balance display
- Humanized operation panel, close to mobile phone operation mode

## SUPPORT

### Skype

## INTERFACES

- USB port ---- 1 X USB1.1 Port connect to PC

## SYSTEM REQUIREMENT:

- Pentium 400MHz or equivalent
- Windows 2000 or XP
- Available USB port (1.0, 1.1 or 2.0)
- Skype version 1.3.0.xx or higher ([www.skype.com](http://www.skype.com)) must be installed
- 128M RAM
- 10M available hard disk space

## OPERATING REQUIREMENT

- Operation temperature: 0 to 40° C ( 32° to 104° F)
- Storage temperature: -30° to 65° C (-22° to 149° F)
- Humidity: 10 to 90% no dew

## REGULATORY COMPLIANCE

- FCC part 15, CE class B